

FICHE DE PRÉ-SÉLECTION CETETHERM AQUACOMPACT

1. AQUACOMPACT = STAINLESS STEEL STORAGE TANK + PRE-ASSEMBLED KIT

AquaCompact units - STANDARD VERSION (without a primary kit)



- Copper brazed
- 100% stainless steel fusion-bonded



- Plates & gaskets



- Plates & gaskets with insulation

- Charging pump
- Balancing valve
- 10 bar pressure relief valve
- Isolating valve and connection pipework and flexible(s)
- Two additional CIP (Cleaning In Place) connections for Copper Brazed and 100% stainless steel heat exchangers

AquaCompact units - WITH A PRIMARY KIT (optional)



- 2-port valve Self-Actuated



- 2-port valve Electronic



- 3-port valve Electronic


2. STORAGE TANK



AquaTank :
Storage tank stainless steel 316Ti
PN 10 bar with Neodul insulation

VOLUME

- 300 L
- 500 L
- 750 L
- 1000 L
- 1500 L

3. CAPACITY IN KW		4. FLOW (L/SEC)			
<input type="text"/>		<input type="text"/>			
5. APPLICATIONS					
<p>Apartments blocks</p>  <input type="text"/> <ul style="list-style-type: none"> Number of apartments Type: studio, 1-bedroom, 2-bedroom... 	<p>Hotels</p>  <input type="text"/> <ul style="list-style-type: none"> Number of rooms Number of stars 	<p>Hospitals / Nursery homes</p>  <input type="text"/> <ul style="list-style-type: none"> Number of rooms Number of beds/room 			
6. TEMPERATURES					
PRIMARY	<input type="checkbox"/> 90°C	<input type="checkbox"/> 80°C	<input type="checkbox"/> 70°C	<input type="checkbox"/> 65°C	<input type="checkbox"/> Other
SECONDARY	<input type="checkbox"/> 10/55°C	<input type="checkbox"/> 10/60°C	<input type="checkbox"/> Other		
7. PRIMARY SIDE CONNECTION					
 <input type="checkbox"/> District heating network		 <input type="checkbox"/> Gas boiler			

Please send your completed file to info.uk@cetetherm.com